



# SNOWPURE

## Water Technologies

### Electropure™ EDI EXL-550

#### New: Higher Quality EDI at Higher Feed Conductivity

##### EXL-550 High TDS EDI Modules

ELECTROPURE™ EXL-550 EDI modules are designed to be the highest rejection EDI modules on the market. EXL is configured to easily build ultrapure water systems with the well-known benefits of Electropure™ EDI technology. The EXL-550 achieves high quality even with 1-Pass RO, saving you money.

ELECTROPURE™ EXL-550 modules have next-generation innovative technology inside. The 550 series is designed to handle higher FCE, Feed Conductivity Equivalent. This means that the EXL-550 will perform well at higher TDS (and CO<sub>2</sub>). As always, EXL includes Electropure's patented Excellion™ membranes, "never-leak" permanent O-ring seals, unique non-scaling electrode system, efficient thin-cell technology, and connections using +GF+ unions.

Electropure™ EDI thin-concentrate technology effectively eliminates scaling. And with Electropure™ EDI technology's excellent mass-transfer design, you don't need salt injection, you don't need feed-and-bleed systems, and you don't need the IONPURE® "all-filled" design.



Parameter	SI Units	US Units
1-Pass RO + GTM Design Flow	3.0 m <sup>3</sup> /h	12 gpm
2-Pass RO Design Flow	4.0 m <sup>3</sup> /h	16 gpm
Maximum Recommended Flow	4.5 m <sup>3</sup> /h	20 gpm
Recovery*	Up to 99%	Up to 99%
Normal Pressure Drop (25°C)	3 bar at 3.5 m <sup>3</sup> /h	45 psi at 16 gpm
Maximum Pressure	7 bar	100 psi

SnowPure recommends Liqui-Cel® GTM for CO<sub>2</sub> removal \* with electrode flow to drain, and concentrate flow recovery

EDI Module Parameters	Recommended for	Maximum
Feedwater Conductivity Equivalent	<9 uS/cm	<43 uS/cm
pH	7.0 to 7.5	5.0 to 9.5
Total Chlorine (as Cl <sub>2</sub> ) and Ozone (O <sub>3</sub> )	ND	ND
Iron (Fe)	ND	<.01 ppm
Manganese (Mn)	ND	<.01 ppm
Sulfide (S <sup>-</sup> )	ND	<.01 ppm
Total Hardness (as CaCO <sub>3</sub> )	<0.5 ppm	<1 ppm
Total Silica (as SiO <sub>2</sub> )	<0.2 ppm	<0.5 ppm
Total Organics (TOC as C)	ND	<0.5 ppm
Temperature	10 to 35C (50-95F)	5 to 45C (40-110F)
Voltage	250VDC	300VDC
Concentrate Flow Direction	Upward	Upward
Feed Flow Direction	Upward	Upward
Dimensions (EXL-550) (WidthxHeightxDepth)	314x606x244 mm (12.4x24x9.6 in)	
Operating Weight (EXL-550)	68 kg (149 lb)	
Shipping Weight (EXL-550)	73 kg (160 lb)	

**SnowPure Water Technologies**  
130 Calle Iglesia  
San Clemente, CA 92672, USA  
Tel: +1.949.240.2188  
[info@snowpure.com](mailto:info@snowpure.com)  
[www.snowpure.com](http://www.snowpure.com)

**SnowPure International, Ltd.**  
Hong Kong  
[info@snowpureintl.com](mailto:info@snowpureintl.com)

**China Sales Office**  
Electropure Environmental  
Technology (Shanghai) Co. Ltd.  
伊乐科环保科技有限公司(上海)有限公司  
Shanghai, China  
[13818807576@163.com](mailto:13818807576@163.com)  
[www.snowpure.com.cn](http://www.snowpure.com.cn)

**Middle East Sales Office**  
Amman, Jordan  
[info@middle-east.snowpure.com](mailto:info@middle-east.snowpure.com)

**India (Authorized Distributor)**  
Evergreen Technologies Pvt. Ltd.  
Mumbai, India  
[info@evergreenindia.com](mailto:info@evergreenindia.com)

**Japan (Authorized Distributor)**  
AMP Ionex / Mihama Group  
美浜株式会社  
Tokyo, Japan  
[info-mhg3@mihama.com](mailto:info-mhg3@mihama.com)  
[www.amp-ionex.com](http://www.amp-ionex.com)

**Korea (Authorized Distributor)**  
Innomedtech, Inc.  
주식회사 이노메디텍  
Seoul, South Korea  
[info@innomt.com](mailto:info@innomt.com)  
[www.innomedtech.co.kr](http://www.innomedtech.co.kr)

**Nordic (Authorized Distributor)**  
PWS Pure Water Scandinavia AB  
Falun, Sweden  
[lars.wiklund@purewater.se](mailto:lars.wiklund@purewater.se)

**Germany (Authorized Distributor)**  
TES Water Treatment GmbH  
Hockenheim, Germany  
[info@tes-water.de](mailto:info@tes-water.de)

**Austria, Switzerland, Czech, Slovakia (Authorized Distributor)**  
ROC Components AG  
Reinach, Switzerland  
[info@roc-ch.com](mailto:info@roc-ch.com)

**South Africa (Authorized Distributor)**  
Marsi Water (Pty) Ltd  
Cape Town, South Africa  
[sales@marsiwater.com](mailto:sales@marsiwater.com)

**Ukraine/Baltics (Authorized Distributor)**  
Nerex PE  
Kyiv, Ukraine  
[com@nerex.ua](mailto:com@nerex.ua)

## Electropure™ EDI Technology

- No concentrate recirculation or brine injection
- Thin-Cell efficient technology
- Thin-Concentrate non-scaling technology
- Unique non-scaling electrode system
- Patented Excellion™ membranes

## Doing business with SnowPure

- Electropure™ EDI technology was born in 1977, before Ionpure
- SnowPure is privately held
- SnowPure is your partner, not a competitor
- High quality Electropure™ EDI training and OEM support

## Benefits of Using EDI

- Continuous Process—no upsets
- Operating cost is minimized
- No hazardous waste, no associated costs and risks
- No regeneration acid or caustic
- Flexible—easy to expand a modular EDI system
- Reliable—no recirculation system components to fail

## EDI Technology Training and OEM System Design Support

- SnowPure believes strongly in training—this helps ensure field success with Electropure™ EDI systems.
- SnowPure assists new OEM customers through their system design phase.
- Our customers also have access to our Best Practices P&ID's to aid in their EDI system optimization.
- Combined with ongoing Technical Service, we help ensure success.



[www.snowpure.com](http://www.snowpure.com)