



# SNOWPURE

## Water Technologies


### Electropure™ EDI XL-SR Modules

#### XL-SR Pharmaceutical EDI Modules

ELECTROPURE™ XL-SR modules are pharmaceutical EDI modules for producing high-resistivity USP Purified Water. They are configured to easily retrofit existing systems with added Electropure™ technology benefits, so the old troublesome Dow Omexell® and GE E-Cell® CONCENTRATE RECIRCULATION IS ELIMINATED.

ELECTROPURE™ XL-SR modules have the compact Electropure profile and have Electropure™ EDI technology inside. This includes Electropure's patented Excellion™ membranes, our unique non-scaling electrode system, and our efficient thin-cell technology.

And with Electropure™ EDI thin-concentrate technology, there is no need for the troublesome Omexell® and E-Cell® recirculation system, so it can be eliminated from the system. With the mass-transfer built into Electropure™ EDI thin-concentrate technology, you don't need either salt injection or feed-and-bleed systems. You also don't need the IONPURE® "all-filled" design.



	<b>XL-100-SR</b>	<b>XL-200-SR</b>	<b>XL-300-SR</b>	<b>XL-400-SR</b>	<b>XL-500-SR</b>
<b>Design Flow</b>	100 l/h	200 l/h	500 l/h	1.0 m3/h	1.7 m3/h
<b>Module Flow</b>	80-150 l/h	100-300 l/h	300-1000 l/h	0.6-1.5 m3/h	1.3-2.5 m3/h
<b>Recovery*</b>	Up to 90%	Up to 95%	Up to 97%	Up to 99%	Up to 99%
<b>Recommended</b>	48 VDC	100 VDC	150 VDC	200 VDC	300 VDC
<b>Normal Pressure</b>	2-3 bar	2-3 bar	2-3 bar	2-3 bar	2-3 bar
<b>Maximum Pres-</b>	5 bar	5 bar	5 bar	5 bar	5 bar

\* with electrolyte to drain, and concentrate recovery

EDI Module Parameters	Recommended for	Maximum
Feedwater Conductivity Equivalent	<9 $\mu$ S/cm	<33 $\mu$ S/cm
pH	7.0 to 7.5	5 to 9.5
Total Chlorine (as Cl <sub>2</sub> ) and Ozone (O <sub>3</sub> )	ND	ND
Iron (Fe)	ND	<.01 ppm
Manganese (Mn)	ND	<.01 ppm
Sulfide (S <sup>-</sup> )	ND	<.01 ppm
Total Hardness (as CaCO <sub>3</sub> )	<0.5 ppm	<1 ppm
Total Silica (as SiO <sub>2</sub> )	<0.2 ppm	<0.5 ppm
Total Organics (TOC as C)	ND	<0.5 ppm
Temperature	15 to 30C (60-85F)	5 to 35C (40-95F)
Concentrate Flow Direction	Upward	Upward
Feed Flow Direction	Upward	Upward
Dimensions (Width x Height x Depth)	22x56xD cm	(8.5x22xD in)
Depth:	<b>XL-100-SR</b> <b>XL-200-SR</b> <b>XL-300-SR</b> <b>XL-400-SR</b> <b>XL-500-SR</b>	

**SnowPure Water Technologies**  
130 Calle Iglesia  
San Clemente, CA 92672, USA  
Tel: +1.949.240.2188  
[info@snowpure.com](mailto:info@snowpure.com)  
[www.snowpure.com](http://www.snowpure.com)

**SnowPure International, Ltd.**  
Hong Kong  
[info@snowpureintl.com](mailto:info@snowpureintl.com)

**China Sales Office**  
Electropure Environmental  
Technology (Shanghai) Co. Ltd.  
伊乐环保科技(上海)有限公司  
Shanghai, China  
[13818807576@163.com](mailto:13818807576@163.com)  
[www.snowpure.com.cn](http://www.snowpure.com.cn)

**Middle East Sales Office**  
Amman, Jordan  
[info@middle-east.snowpure.com](mailto:info@middle-east.snowpure.com)

**India (Authorized Distributor)**  
Evergreen Technologies Pvt. Ltd.  
Mumbai, India  
[info@evergreenindia.com](mailto:info@evergreenindia.com)

**Japan (Authorized Distributor)**  
AMP Ionex / Mihama Group  
美浜株式会社  
Tokyo, Japan  
[info-mhg3@mihama.com](mailto:info-mhg3@mihama.com)  
[www.amp-ionex.com](http://www.amp-ionex.com)

**Korea (Authorized Distributor)**  
Innomeditech, Inc.  
주식회사 이노메디텍  
Seoul, South Korea  
[info@innomt.com](mailto:info@innomt.com)  
[www.innomeditech.co.kr](http://www.innomeditech.co.kr)

**Nordic (Authorized Distributor)**  
PWS Pure Water Scandinavia AB  
Falun, Sweden  
[lars.wiklund@purewater.se](mailto:lars.wiklund@purewater.se)

**Germany (Authorized Distributor)**  
TES Water Treatment GmbH  
Hockenheim, Germany  
[info@tes-water.de](mailto:info@tes-water.de)

**Austria, Switzerland, Czech, Slovakia (Authorized Distributor)**  
ROC Components AG  
Reinach, Switzerland  
[info@roc-ch.com](mailto:info@roc-ch.com)

**South Africa (Authorized Distributor)**  
Marsi Water (Pty) Ltd  
Cape Town, South Africa  
[sales@marsiwater.com](mailto:sales@marsiwater.com)

**Ukraine/Baltics (Authorized Distributor)**  
Nerex PE  
Kyiv, Ukraine  
[com@nerex.ua](mailto:com@nerex.ua)

### Electropure™ EDI Technology

- No concentrate recirculation or brine injection
- Thin-Cell efficient technology
- Thin-Concentrate non-scaling technology
- Unique non-scaling electrode system
- Patented Excellion™ membranes

### Doing business with SnowPure

- Electropure™ EDI technology was born in 1977, before Ionpure
- SnowPure is privately held
- SnowPure is your partner, not a competitor
- High quality Electropure™ EDI training and OEM support

### Benefits of Using EDI

- Continuous Process-no upsets
- Operating cost is minimized
- No hazardous waste, no associated costs and risks
- No regeneration acid or caustic
- Flexible—easy to expand a modular EDI system
- Reliable—no recirculation system components to fail

### EDI Technology Training and OEM System Design Support

- SnowPure believes strongly in training—this helps ensure field success with Electropure™ EDI systems.
- SnowPure assists new OEM customers through their system design phase.
- Our customers also have access to our Best Practices P&ID's to aid in their EDI system optimization.
- Combined with ongoing Technical Service, we help ensure success.

