

SnowPure's DC Power Product Line

O-008F: 25kW 0-10Vdc Interface DC Power Supply Designed For EDI

SnowPure has designed another modular DC switching power supply for its Electropure™ brand EDI modules:

- Air-cooled, switch-mode rectifier
- Designed for continuous operation at rated output
- Constant low ripple of less than 3%
- Power semiconductors for pulse amplitude modulation
- Electronics for constant voltage control
- Over-current and short-circuit protection
- Over-temperature protection
- Suitable for NEMA Enclosures, flange mount
- 0-600VDC, 0-40ADC, 25kW
- Designed for:
 - EXL-850 x 5-6 modules (0-600VDC, operates at 500VDC)
- Interlock by dry normally open contact (flow switch or pressure switch)
- CE Compliant
- EMC filter
- Standard 0-10Vdc Interface– Optional System Controls:
 - O-016 For customer supplied PLC, 4-20mA
 - O-016A For customer supplied PLC, Modbus RS485



Electrical Parameter	Specification Value
Output DC Voltage (Constant Voltage Mode)	0-600 VDC
Output DC Current (Has Overcurrent Protection)	0-40 Amps DC (ADC)
AC Input (to be specified in this range)	380-480VAC/3PH/50-60HZ

ediPureSource™ O-008F Features	Specification
Protection: Over-Current (Lowers Operating Voltage)	@40.1 ADC
Protection: Over-Current (Shutdown/Fault)	@41-43 ADC
Protection: Short-Circuit (Shutdown/Fault)	Included
Protection: Over-Temperature (Standby/Fault)	Included
Cooling: Speed Controlled Fan	Inlet: Front, Outlet: Rear
Voltage Ripple, Max (Operation)	< 3% (1-2%)
Power Efficiency Rating (@Full Load)	> 94%
System Interfaces & Options	Setpoint adjustment for V+A: 0-10Vdc (standard) 4-20mA Control Interface card (option O-016) Modbus RS485 Control Interface card (option O-016A) Remote Volt/Amp On/Off/Set/Display (option O-016B) Main input contactor "On/Off" (customer) Interlock "Open/Closed" (customer) Fault Indicator (customer)
Voltage and Current	Actual: 0-10Vdc (customer, optional O-016B)
CE Compliance	Low Voltage Directives: IEC EN61558-2-16, EN61558-1
Mounting	Flange/Bottom, Optional Flange/Front
Degree of Protection	NEMA 2
Dimensions (O-008F) (Width x Depth x height)	19.3x18.9x10.9 inches 49x48x27.7 cm
Operating Weight	95 lbs (43 kg)

SnowPure Water Technologies

130 Calle Iglesia
San Clemente, CA 92672, USA
Tel: +1.949.240.2188
info@snowpure.com
www.snowpure.com

SnowPure International, Ltd.

Hong Kong
Tel: +852.95127229
info@snowpureintl.com
www.snowpureintl.com

India (Authorized Distributor)

Evergreen Technologies Pvt. Ltd.
Tel: +91.2201.2461
info@evergreenindia.com
www.evergreenindia.com

Japan (Authorized Distributor)

AMP Ionex / Mihama
美浜株式会社
Tel: +81.3.4570.3819
info-mhg3@mihama.com
www.mihama.com

Korea (Authorized Distributor)

Innomeditech, Inc.
주식회사 인노메디텍
Tel: +82.31.8002.2500
info@innomt.com
www.innomeditech.co.kr

Nordic/Baltic (Authorized Distributor)

PWS Pure Water Scandinavia AB
Tel: +46.23.797990
lars.wiklund@purewater.se
www.purewater.se

Switzerland, Austria, Czech Republic, Slovakia

(Authorized Distributor)
ROC Components AG
Tel: +41.61.461.83.03
info@roc-ch.com
www.roc-ch.com

China Sales Office

Electropure Environmental
Technology (Shanghai) Co. Ltd.
伊乐环保科技(上海)有限公司
Tel: +86.21.6167.1860
sds1235@163.com
www.snowpure-edi.com.cn

South Africa (Authorized Distributor)

Marsi Water (Pty) Ltd.
Tel: +27.21.701.0644
pierre@marsiwater.com
www.marsiwater.com

Middle East (Authorized Distributor)

Tafaseel Engineering Est.
Tel: +962.64.16.6555
daour@tafaseel-eng.com
www.tafaseel-eng.com

Electropure™ EDI Technology

- No concentrate recirculation or brine injection
- Thin-Cell efficient technology
- Thin-Concentrate non-scaling technology
- Unique non-scaling electrode system
- Patented Excellion™ membranes

Doing business with SnowPure

- Electropure™ EDI technology was born in 1977, before Ionpure®
- SnowPure is privately held
- SnowPure is your partner, not a competitor
- High quality Electropure™ EDI training and OEM support

Benefits of Using EDI

- Continuous Process-no upsets
- Operating cost is minimized
- No hazardous waste, no associated costs and risks
- No regeneration acid or caustic
- Flexible—easy to expand a modular EDI system
- Reliable—no recirculation system components to fail

EDI Technology Training and OEM System Design Support

- SnowPure believes strongly in training—this helps ensure field success with Electropure™ EDI systems.
- SnowPure assists new OEM customers through their system design phase.
- Our customers also have access to our Best Practices P&ID's to aid in their EDI system optimization.
- Combined with ongoing Technical Service, we help ensure success.